

INSTALLATION INSTRUCTIONS

HONDA REBEL 1100 GRIP INSTALLATION

KIT CONTENTS



QTY	DESCRIPTION
1	BURLY SLASH CUT HANDLEGRIP -RIGHT THROTTLE BY WIRE SIDE
1	BURLY SLASH CUT HANDLEGRIP – LEFT CLUTCH SIDE
2	M4 SET SCREWS
1	ALLEN WRENCH

LIMITED GUARANTEE

We continually inspect and try to improve our products. All parts have been inspected prior to packaging, and our guarantee is limited to replacement of defective parts. This guarantee is in lieu of all guarantees or warranties implied or expressed. Because we can not control the application of our products, the buyer assumes risks for any and all damage caused by themselves or any third party, by virtue of failure of these parts. We make no warranty as to products distributed by us, expressed or implied, including without limitation, any warranties or merchant ability and fitness for particular purpose. We will, however, pass on all warranties made by the manufacturer, who has sole responsibility for performing such warranties. The manufacturer shall solely be responsible for any damage to person or property arising from design, manufacturing and testing of all products, and we accept no liability for such damages. We shall not be liable for indirect or consequential damages.

INSTALLATION INSTRUCTIONS

HONDA REBEL 1100 GRIP INSTALLATION THROTTLE SIDE


WARNINGS & ALERTS:

- READ AND FOLLOW ALL INSTRUCTIONS TO PROPERLY INSTALL THIS KIT.
- IMPROPER INSTALLATION CAN CAUSE UNSATISFACTORY AND/OR UNSAFE OPERATION.

1. Loosen the two socket head cap screws that clamp onto the controls to access the two Phillip head screws that connect the front and back plastic housings together.



2. Remove the bar end M6 x 1mm socket head cap screw using an Allen key or a hex socket.
3. Remove the two Phillips head control housing screws. Split the front and back switch housings.



4. Remove one Phillips head screw that attaches to the back housing.
5. Split the front and back housings so you can clear the groove on the throttle grip and carefully slide the grip out.
6. Slide the new Burly grip until the throttle sensor teeth engage. Note: the tab on the Burly grip should be pointing in the downward direction as shown



7. Make sure the Flange of the throttle grip fits within the throttle switch housing.




8. Position the front and back switch housing on the handlebar. Tighten the one Phillips head screw that attaches to the back housing. Next, connect the front and back housings together and tighten the two Phillips screws from the backside. Torque to factory spec.
9. Verify the throttle functions properly and moves freely with no binding.



INSTALLATION INSTRUCTIONS

HONDA REBEL 1100 GRIP INSTALLATION CLUTCH SIDE

1. To remove the stock rubber grip, remove the bar M6 x 1mm socket head cap screw using an Allen key or a hex socket.
2. Use a long flat head screwdriver to loosen the rubber grip to create a gap between the grip and the handlebar.



3. Using isopropyl alcohol, spray under and over the grip. Remove the stock grip using a pulling and twisting motion. If the rubber grip is hard to remove, spray more isopropyl alcohol in between the grip and the handlebar.
4. Clean and wipe down the handlebar surface.
5. Slide on the new left side grip until the grip stops against the switch housing. Look at the end of the grip to position the logo where you prefer. Mark the set screw locations through the threaded holes using a transfer punch and a hammer.
6. Using a 1/8th center drill, drill two small dimples into the bar. This will ensure the grip will not rotate when the set screws are installed.
7. Use high strength thread locking compound and the supplied Allen key to tighten the two set screws on the grip. Make sure the grip is secured. Allow the thread locking compound to fully cure before riding.

